

Diesel Engine

Heat Exchanger Series

Specification

Engine Model		FD475
Туре	Vertical, water-cooling, 4-stroke, direct-injector	
Aspiration		Turbocharged
Number of Cylinders		4
Bore x Stoke (mm)		100x105
Compression Ratio		18:1
Total Displacement (L)		3.29L
Rated Power	KW	55
Rated Speed	r/min	3000
Max. torque	N.m	≥158.7
Fuel Consumption	g/kW.h	≤228
Cooling System		Heat Exchanger
Rotating Direction at Output End		Counter-clockwise
Lubrication Oil		15W40
Lubrication Oil Content	L	6.5
Lubrication Method		Pressure and splash
Starting Method		Electric
vvvPT0 Type		Option:1. Shaft
		2. Coupling
		3. Drive Plate
Net Mass	kg	300









160 Robinson Road, #14-04 Singapore Business Federation Center Singapore (068914)















■ FIRETECH System Privet Limited in USA Address: 7727 249TH STREET BELLEROSE, NY, UNITED STATES Email: info@firetech-sg.com

FIRETECH System Privet Limited in Singapore
Address: 160 Robinson Road, #14-04 Singapore Business Federation Center Singapore (068914)
Email: inquiry@firetech-sg.com



